

Package: mulSEM (via r-universe)

October 14, 2026

Type Package

Title Some Multivariate Analyses using Structural Equation Modeling

Version 1.2

Date 2026-02-16

Depends R (>= 4.3.0), OpenMx

Imports stats

Encoding UTF-8

Description A set of functions for some multivariate analyses utilizing a structural equation modeling (SEM) approach through the 'OpenMx' package. These analyses include canonical correlation analysis (CANCORR), redundancy analysis (RDA), and multivariate principal component regression (MPCR). It implements procedures discussed in Gu and Cheung (2023) [doi:10.1111/bmsp.12301](https://doi.org/10.1111/bmsp.12301), Gu, Yung, and Cheung (2019) [doi:10.1080/00273171.2018.1512847](https://doi.org/10.1080/00273171.2018.1512847), and Gu et al. (2023) [doi:10.1080/00273171.2022.2141675](https://doi.org/10.1080/00273171.2022.2141675).

License GPL (>=2)

LazyLoad yes

LazyData yes

ByteCompile yes

URL <https://github.com/mikewlcheung/mulsem>

BugReports <https://github.com/mikewlcheung/mulsem/issues>

Suggests roxygen2

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.3

Config/pak/sysreqs cmake make

Repository <https://mikewlcheung.r-universe.dev>

Date/Publication 2026-02-16 14:16:56 UTC

RemoteUrl <https://github.com/mikewlcheung/mulsem>

RemoteRef HEAD

RemoteSha 505d5367ef47171979b7de02be65e9f2e28c49fa

Contents

cancorr	2
Chittum19	3
Lambert88	4
mper	5
Nimon21	7
print.CanCorr	8
print.MPCR	8
print.RDA	9
rda	10
sas_ex1	11
sas_ex2	12
Thorndike00	12
Index	14

cancorr	<i>Canonical correlation analysis</i>
---------	---------------------------------------

Description

This function conducts canonical correlation analysis using the OpenMx package. Missing data are handled with the full information maximum likelihood method when raw data are available. It provides standard errors for the estimates.

Usage

```
cancorr(  
  X_vars,  
  Y_vars,  
  data = NULL,  
  Cov = NULL,  
  numObs = NULL,  
  model = c("CORR-W", "CORR-L", "COV-W", "COV-L"),  
  extraTries = 50,  
  ...  
)
```

Arguments

X_vars	A vector of characters of the X variables.
Y_vars	A vector of characters of the Y variables.
data	A data frame containing raw data. If NULL, Cov and numObs must be provided.
Cov	A covariance or correlation matrix. Required when data is NULL.
numObs	A sample size. Required when data is NULL.

model	Four models defined in Gu, Yung, and Cheung (2019). CORR and COV refer to analyses of correlation structures and covariance structures, respectively.
extraTries	This function calls <code>OpenMx::mxTryHard()</code> to obtain parameter estimates and their standard errors. extraTries is the number of extra runs. If extraTries=0, <code>OpenMx::mxRun()</code> is called.
...	Additional arguments passed to either <code>OpenMx::mxTryHard()</code> or <code>OpenMx::mxRun()</code> .

Value

A list with class CanCorr. It stores the model in OpenMx objects. The fitted object is stored in `mx.fit`.

Note

cancorr expects the number of variables in Y_vars to be equal to or greater than that in X_vars. If there are fewer in Y_vars, you may swap between X_vars and Y_vars.

Author(s)

Mike W.-L. Cheung mikewlcheung@nus.edu.sg

References

Gu, F., Yung, Y.-F., & Cheung, M. W.-L. (2019). Four covariance structure models for canonical correlation analysis: A COSAN modeling approach. *Multivariate Behavioral Research*, **54**(2), 192-223. doi:[10.1080/00273171.2018.1512847](https://doi.org/10.1080/00273171.2018.1512847)

See Also

[Thorndike00, sas_ex1](#)

Examples

```
## Canonical Correlation Analysis
cancorr(X_vars=c("Weight", "Waist", "Pulse"),
        Y_vars=c("Chins", "Situps", "Jumps"),
        data=sas_ex1)
```

Chittum19	<i>Correlation matrix of a model of motivation</i>
-----------	--

Description

This dataset includes a correlation matrix of 12 variables (n=533) of a model of motivation reported by Chittum, Jones, and Carter (2019).

Usage

Chittum19

Format

A list with the following components:

data A 12x12 correlation matrix.

n A sample size (533).

Source

Chittum, J. R., Jones, B. D., & Carter, D. M. (2019). A person-centered investigation of patterns in college students' perceptions of motivation in a course. *Learning and Individual Differences*, **69**, 94-107. doi:10.1016/j.lindif.2018.11.007

References

Gu, F., Yung, Y.-F., Cheung, M. W.-L., Joo, B.-K., & Nimon, K. (2023). Statistical inference in redundancy analysis: A direct covariance structure modeling approach. *Multivariate Behavioral Research*, **58**(5), 877-893. doi:10.1080/00273171.2022.2141675

Examples

```
data(Chittum19)

## Redundancy Analysis
rda(X_vars=c("Empowerment", "Usefulness", "Success", "Interest", "Caring"),
    Y_vars=c("Final_Exam", "Learning", "Course_Rating", "Instr_Rating",
             "Effort", "Cog_Engage", "Cost"),
    Cov=Chittum19$data, numObs=Chittum19$n)
```

Lambert88

Correlation matrix of artificial data

Description

This dataset includes a correlation matrix of nine artificial variables used in Table 1 of Lambert, Wildt, and Durand (1988).

Usage

Lambert88

Format

A 9x9 correlation matrix.

Source

Lambert, Z. V., Wildt, A. R., & Durand, R. M. (1988). Redundancy analysis: An alternative to canonical correlation and multivariate multiple regression in exploring interset associations. *Psychological Bulletin*, **104**(2), 282-289. doi:[10.1037/00332909.104.2.282](https://doi.org/10.1037/00332909.104.2.282)

References

Gu, F., Yung, Y.-F., Cheung, M. W.-L., Joo, B.-K., & Nimon, K. (2023). Statistical inference in redundancy analysis: A direct covariance structure modeling approach. *Multivariate Behavioral Research*, **58**(5), 877-893. doi:[10.1080/00273171.2022.2141675](https://doi.org/10.1080/00273171.2022.2141675)

Examples

```
data(Lambert88)

## Redundancy Analysis
rda(X_vars=paste0("x", 1:5), Y_vars=paste0("y", 1:4), Cov=Lambert88, numObs=100)
```

mpcr

Multivariate Principal Component Regression (MPCR)

Description

Conduct multivariate principal component regression

Usage

```
mpcr(
  X_vars,
  Y_vars,
  data = NULL,
  Cov = NULL,
  Means = NULL,
  numObs = NULL,
  pca = c("COV", "COR"),
  pc_select = NULL,
  extraTries = 50,
  ...
)
```

Arguments

<code>X_vars</code>	A vector of characters of the X variables.
<code>Y_vars</code>	A vector of characters of the Y variables.
<code>data</code>	A data frame containing raw data. If NULL, Cov and numObs must be provided.

Cov	A covariance or correlation matrix. Required when data is NULL.
Means	An optional mean vector. Can be provided when data is NULL.
numObs	A sample size. Required when data is NULL.
pca	Whether principal component analysis is based on unstandardized (COV) or standardized (COR) variables.
pc_select	PCs selected in the regression analysis. For example, <code>pc_select=c(1,2)</code> to use the first two PCs in the multiple regression analysis.
extraTries	This function calls <code>OpenMx::mxTryHard()</code> to obtain parameter estimates and their standard errors. <code>extraTries</code> is the number of extra runs. If <code>extraTries=0</code> , <code>OpenMx::mxRun()</code> is called.
...	Additional arguments passed to either <code>OpenMx::mxTryHard()</code> or <code>OpenMx::mxRun()</code> .

Details

This function conducts multivariate principal component regression using the OpenMx package. Missing data are handled with the full information maximum likelihood method when raw data are available. It provides standard errors for the estimates.

Value

A list with class `MPCR`. It stores the model in OpenMx objects. The fitted object is stored in `mx.fit`.

Author(s)

Mike W.-L. Cheung mikewlcheung@nus.edu.sg

References

Gu, F., & Cheung, M. W.-L. (2023). A model-based approach to multivariate principal component regression: Selection of principal components and standard error estimates for unstandardized regression coefficients. *British Journal of Mathematical and Statistical Psychology*, **76**(3), 605-622. [doi:10.1111/bmsp.12301](https://doi.org/10.1111/bmsp.12301)

See Also

[Nimon21](#)

Examples

```
## Multivariate Principal Component Regression
mpcr(X_vars=c("AU", "CC", "CL", "CO", "DF", "FB", "GR", "MW"),
     Y_vars=c("IDE", "IEE", "IOCB", "IPR", "ITS"),
     pca="COR", pc_select=1,
     data=Nimon21)
```

Nimon21Raw data used in Nimon, Joo, and Bontrager (2021)

Description

This dataset includes the raw data of 13 variables reported by Nimon, Joo, and Bontrager (2021).

Usage

Nimon21

Format

A data frame with 13 variables.

Source

Nimon, K., Joo, B.-K. (Brian), & Bontrager, M. (2021). Work cognitions and work intentions: A canonical correlation study. *Human Resource Development International*, **24**(1), 65-91. doi:10.1080/13678868.2020.1775038

References

Gu, F., & Cheung, M. W.-L. (2023). A Model-based approach to multivariate principal component regression: Selection of principal components and standard error estimates for unstandardized regression coefficients. *British Journal of Mathematical and Statistical Psychology*, **76**(3), 605-622. doi:10.1111/bmsp.12301

Gu, F., Yung, Y.-F., Cheung, M. W.-L., Joo, B.-K., & Nimon, K. (2023). Statistical inference in redundancy analysis: A direct covariance structure modeling approach. *Multivariate Behavioral Research*, **58**(5), 877-893. doi:10.1080/00273171.2022.2141675

Examples

```
data(Nimon21)

## Redundancy Analysis
rda(X_vars=c("AU", "CC", "CL", "CO", "DF", "FB", "GR", "MW"),
    Y_vars=c("IDE", "IEE", "IOCB", "IPR", "ITS"),
    data=Nimon21)

## Multivariate Principal Component Regression
mpcr(X_vars=c("AU", "CC", "CL", "CO", "DF", "FB", "GR", "MW"),
     Y_vars=c("IDE", "IEE", "IOCB", "IPR", "ITS"),
     pca="COR", pc_select=1,
     data=Nimon21)
```

print.CanCorr	<i>Print Method for CanCorr Objects</i>
---------------	---

Description

Print method for CanCorr objects.

Usage

```
## S3 method for class 'CanCorr'  
print(x, digits = 4, ...)
```

Arguments

x	An object returned from the class of CanCorr.
digits	Number of digits in printing the matrices. The default is 4.
...	Unused.

Value

No return value, called for side effects

Author(s)

Mike W.-L. Cheung mikewlcheung@nus.edu.sg

print.MPCR	<i>Print Method for MPCR Objects</i>
------------	--------------------------------------

Description

Print method for MPCR objects.

Usage

```
## S3 method for class 'MPCR'  
print(x, digits = 4, ...)
```

Arguments

x	An object returned from the class of MPCR.
digits	Number of digits in printing the matrices. The default is 4.
...	Unused.

Value

No return value, called for side effects

Author(s)

Mike W.-L. Cheung mikewlcheung@nus.edu.sg

<code>print.RDA</code>	<i>Print Method for RDA Objects</i>
------------------------	-------------------------------------

Description

Print method for RDA objects.

Usage

```
## S3 method for class 'RDA'  
print(x, digits = 4, ...)
```

Arguments

<code>x</code>	An object returned from the class of RDA.
<code>digits</code>	Number of digits in printing the matrices. The default is 4.
<code>...</code>	Unused.

Value

No return value, called for side effects

Author(s)

Mike W.-L. Cheung mikewlcheung@nus.edu.sg

rda	<i>Redundancy analysis</i>
-----	----------------------------

Description

This function conducts redundancy analysis using the OpenMx package. Missing data are handled with the full information maximum likelihood method when raw data are available. It provides standard errors for the standardized estimates.

Usage

```
rda(
  X_vars,
  Y_vars,
  data = NULL,
  Cov = NULL,
  numObs = NULL,
  extraTries = 50,
  ...
)
```

Arguments

<code>X_vars</code>	A vector of characters of the X variables.
<code>Y_vars</code>	A vector of characters of the Y variables.
<code>data</code>	A data frame containing raw data. If NULL, <code>Cov</code> and <code>numObs</code> must be provided.
<code>Cov</code>	A covariance or correlation matrix. Required when <code>data</code> is NULL.
<code>numObs</code>	A sample size. Required when <code>data</code> is NULL.
<code>extraTries</code>	This function calls <code>OpenMx::mxTryHard()</code> to obtain parameter estimates and their standard errors. <code>extraTries</code> is the number of extra runs. If <code>extraTries=0</code> , <code>OpenMx::mxRun()</code> is called.
<code>...</code>	Additional arguments passed to either <code>OpenMx::mxTryHard()</code> or <code>OpenMx::mxRun()</code> .

Value

A list with class RDA. It stores the model in OpenMx objects. The fitted object is stored in `mx.fit`.

Author(s)

Mike W.-L. Cheung mikewlcheung@nus.edu.sg

References

Gu, F., Yung, Y.-F., Cheung, M. W.-L., Joo, B.-K., & Nimon, K. (2023). Statistical inference in redundancy analysis: A direct covariance structure modeling approach. *Multivariate Behavioral Research*, **58**(5), 877-893. doi:10.1080/00273171.2022.2141675

See Also[Chittum19, sas_ex2](#)**Examples**

```
## Redundancy Analysis
rda(X_vars=c("x1", "x2", "x3", "x4"),
    Y_vars=c("y1", "y2", "y3"),
    data=sas_ex2)
```

sas_ex1*Sample data for canonical correlation analysis from the SAS manual*

Description

This dataset includes six variables of fitness club data from the SAS manual.

Usage

```
sas_ex1
```

Format

A data frame with 20 rows and 6 variables:

Weight Weight measurement

Waist Waist measurement

Pulse Pulse measurement

Chins Number of chin-ups

Situps Number of sit-ups

Jumps Number of jumps

Source

https://documentation.sas.com/doc/en/statcdc/14.2/statug/statug_cancorr_example01.htm

Examples

```
data(sas_ex1)
```

```
## Canonical Correlation Analysis
cancorr(X_vars=c("Weight", "Waist", "Pulse"),
        Y_vars=c("Chins", "Situps", "Jumps"),
        data=sas_ex1)
```

sas_ex2

Sample data for redundancy analysis from the SAS manual

Description

This dataset includes seven variables from the SAS manual.

Usage

sas_ex2

Format

A matrix with 10 rows and 7 columns:

y1, y2, y3 Y variables

x1, x2, x3, x4 X variables

Source

https://documentation.sas.com/doc/en/pgmsascdc/9.4_3.3/statug/statug_transreg_details23.htm

Examples

```
data(sas_ex2)
```

```
## Redundancy Analysis
rda(X_vars=c("x1", "x2", "x3", "x4"),
    Y_vars=c("y1", "y2", "y3"),
    data=sas_ex2)
```

Thorndike00

Correlation matrix of a model of disgust

Description

This dataset includes a correlation matrix of 13 variables (n=679) between five subscales (y1 to y5) of the Disgust Emotion Scale and eight subscales (x1 to x8) of the Disgust Scale reported by Thorndike (2000, p. 238).

Usage

Thorndike00

Format

A list with the following components:

data A 13x13 correlation matrix.

n A sample size (679).

Source

Thorndike, R. M. (2000). Canonical correlation analysis. In H. E. A. Tinsley & S. D. Brown (Eds.), *Handbook of applied multivariate statistics and mathematical modeling* (pp. 237-263). San Diego, CA: Academic Press.

References

Gu, F., Yung, Y.-F., & Cheung, M. W.-L. (2019). Four covariance structure models for canonical correlation analysis: A COSAN modeling approach. *Multivariate Behavioral Research*, **54**(2), 192-223. doi:10.1080/00273171.2018.1512847

Examples

```
data(Thorndike00)

## Canonical Correlation Analysis
## Note. We swap the X_vars and Y_vars because cancrr() expects that
## X_vars cannot have more variables than Y_vars.

cancrr(X_vars=c("y1", "y2", "y3", "y4", "y5"),
        Y_vars=c("x1", "x2", "x3", "x4", "x5", "x6", "x7", "x8"),
        Cov=Thorndike00$data, numObs=Thorndike00$n)
```

Index

* datasets

- Chittum19, [3](#)
- Lambert88, [4](#)
- Nimon21, [7](#)
- sas_ex1, [11](#)
- sas_ex2, [12](#)
- Thorndike00, [12](#)

cancorr, [2](#)

Chittum19, [3](#), [11](#)

Lambert88, [4](#)

mpcr, [5](#)

Nimon21, [6](#), [7](#)

OpenMx::mxRun(), [3](#), [6](#), [10](#)

OpenMx::mxTryHard(), [3](#), [6](#), [10](#)

print.CanCorr, [8](#)

print.MPCR, [8](#)

print.RDA, [9](#)

rda, [10](#)

sas_ex1, [3](#), [11](#)

sas_ex2, [11](#), [12](#)

Thorndike00, [3](#), [12](#)